



## Arius NTS (No Toe Stop) Aluminum Plates

Plate size	Riedell boot size	Plate length in mm	Wheelbase in mm	Toe length* in mm	Heel length** in mm	Plate length in inches	Wheelbase in inches	Plate weight each / pair in ounces	Plate assembly weight*** each / pair in ounces
3	3, 3 1/2	210	134	45	30	8 1/4	5 1/4	6.91 / 13.82	13.19 / 26.38
4	4, 4 1/2	220	144	45	30	8 2/3	5 2/3	7.02 / 14.04	13.30 / 26.60
5	5, 5 1/2	226	150	45	30	8 9/10	5 9/10	7.12 / 14.24	13.40 / 26.80
6	6, 6 1/2	232	156	45	30	9 1/8	6 1/8	7.23 / 14.46	13.51 / 27.02
7	7, 7 1/2	238	162	45	30	9 7/20	6 3/8	7.34 / 14.68	13.62 / 27.24
8	8, 8 1/2	244	168	45	30	9 3/5	6 5/8	7.44 / 14.88	13.72 / 27.44
9	9, 9 1/2	250	174	45	30	9 17/20	6 17/20	7.55 / 15.10	13.83 / 27.66
10	10, 10 1/2	256	180	45	30	10 1/10	7 1/10	7.65 / 15.30	13.93 / 27.86
11	11, 11 1/2	262	186	45	30	10 3/10	7 1/3	7.76 / 15.52	14.04 / 28.08
12	12, 12 1/2	268	192	45	30	10 11/20	7 9/16	7.87 / 15.74	14.15 / 28.30
13	13	274	198	45	30	10 4/5	7 4/5	7.97 / 15.94	14.25 / 28.50

\*Toe length is distance from center of front axle to front end of plate

\*\*Heel length is distance from center of back axle to back end of plate

\*\*\*Plate assembly includes Axis Pins, trucks, Butterfly Cushions, lock nuts

This chart is a guide - recommendations from the manufacturer. Plate size and mounting can vary for skaters. Skates mounted at Riedell will use this guide unless otherwise specified.